


NOTES:

1. VIEWING ANGLE: 6:00 0' CLOCK
2. DISPLAY MODE: POSITIVE/REFLECTIVE/TN TYPE
3. DRIVING VOLTAGE: 5.0V, DUTY: 1/8, BIAS: 1/4, FREQUENCY: 64HZ
4. OPERATING TEMP.: 0° C TO 50° C
5. STORAGE TEMP.: -10° C TO 60° C
6. CONNECTOR: FLEXIBLE (RUBBER TYPE)
7. THERE ARE MANY CROSSING IN THE VIEW



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
COM1	1D	2D	3D	4D	5	6	7	8	9	10	11	12	13	14	15	16
COM2	1E	2E	3E	4E	11	3	5	LIFT	COM2	COM3	COM4	COM5	COM6	COM7	COM8	
COM3	1C	2C	3C	4C	13	4	6	TO								
COM4	1G	2G	3G	4G	15	7	8	T1								
COM5	1F	2F	3F	4F	17	9	10	T2								
COM6	1B	2B	3B	4B	16		12	T3								
COM7	1A	2A	3A	4A	FACE		14	CONT1								
COM8	1	S1	S2	S3												COM8

VER.	MODIFY	CONTENTS	DATE	DESIGN	APP	BY
1						
2						
3						
4						
5						
6						

		GD-4470M	
PART NO.		GD-4470M	
DESIGN BY			
CHECKED BY			
APP			

XIAMEN OCULAR LCD DEVICES CO., LTD	
TOLERANCES UNLESS OTHERWISE STATED	
.X ±0.20	ANGLES ±1°
.XX ±0.10	ALL DIMENSIONS IN MM
UNLESS OTHERWISE STATED	
CUSTOMER:	
COMPOSE TYPE:	
DRONE	MM
MM	MM
APPLICATION:	
<input type="checkbox"/> Instrument	<input type="checkbox"/> Medical/Book
<input type="checkbox"/> Telephone	<input type="checkbox"/> Automobile
<input type="checkbox"/> Home Appliances	<input type="checkbox"/> Air-condition
<input type="checkbox"/> Other	<input type="checkbox"/> No
SAMPLE: <input type="checkbox"/> Yes <input type="checkbox"/> No	